

New 1W+2W Fixed Input with Continuous Short Circuit Protection MOTIEN TECHNOLOGY specializes in DC/DC Converters and is proud to present the new product – NP1+NP2 Series

Feature:

- ✓ 1W+ 2W Power rating / SIP 7
- ✓ Efficiency is up to 84% (NP1) & 87% (NP2)
- ✓ Continuous Short Circuit Protection
- ✓ 3000 / 6000 VDC Isolation

✓ Operating temperature: -40°C~+95 °C (NP1)

-40°C~+90 °C (NP2)

Comparison with MOTIEN existing products :

	NP1	V1	V1P	T1
Package	SIP7	SIP7	SIP7	SIP7
Pinout compatibility	Compatible			
Short Circuit Protection	YES	NO	YES	YES
Capacitor Load	220~3300 μF	100~220 μF	100~220 μF	47~220 μF
Isolation Voltage	3000 Vdc / 6000 Vdc	1000~6000Vdc	1000~6000Vdc	1500~3000Vdc
Case Temperature	115 ℃	100 ℃	100 ℃	115 °C
Operating Temperature	-40~95 ℃	-40~85 ℃	-40~85 ℃	-40~105 ℃
Safety	Functional Insulation	Functional Insulation IEC/EN/UL 60950-1, 62368-1	Functional Insulation	Functional Insulation

	NP2	V3	
Package	SIP7	SIP7	
Pinout compatibility	Compatible		
Short Circuit Protection	YES	No	
Capacitor Load	220~3300 μF	220~470 μF	
Isolation Voltage	3000 VDC / 6000 VDC	1000~6000Vdc	
Case Temperature	115 ℃	100 ℃	
Operating Temperature	-40~90 ℃	-40~85 ℃	
Safety	Functional Insulation	Functional Insulation	



