







MOTIEN open frame SMD products feature with ultra Compact size and high efficiency. They are qualified for Lead-free Reflow Solder Process and complied with IPC/JEDEC J-STD-020D.1 Level 1. All products are available with optional packages in packing tube and tape & reel packing.

| Series | Watt | Input Range | Efficiency | Isolation Voltage | Package | Features | Certification | Picture |
|----------|---------|--|------------|-------------------|-----------|--|---|---|
| SVRH-0.5 | 1.65~6W | 48 - 9~72V 48 - 14~72V 48 - 17~72V 48- 21~72V | 92% | Non-Isolated | SMD 10PIN | <ol style="list-style-type: none"> 1. Non-Isolated Regulator 2. Adjustable Output Voltage 3. Continuous Short Circuit Protection 4. Remote ON/OFF Control 5. Excellent Line / Load Regulation 6. Operation Temperature Range -40°C~+105°C |   |  |
| SVR-1.0 | 1.2~15W | 5 - 3~5.5V 24 - 4.6~36V | 96% | Non-Isolated | SMD 10PIN | <ol style="list-style-type: none"> 1. Non-Isolated Regulator with very low standby current 2. Adjustable Output Voltage 3. Continuous Short Circuit Protection 4. Low Ripple and Noise 5. Remote ON/OFF Control 6. Excellent Line / Load Regulation 7. Operation Temperature Range -40°C~+105°C |   |  |

