

模甸科技提供完整的高隔離耐壓系列直流對直流轉換器，加強絕緣通過IEC/EN/UL 62368-1 安全標準認證，具有 5 kVAC / 1 分鐘隔離 (250 ~ 300 VAC 工作電壓)，還提供不同的包裝和不同的輸出功率選擇。

除以下型號外，其餘模甸系列均為功能性隔離等級。

Series	Power (W)	Input voltage range (VDC)	Output voltage (VDC)	Isolation voltage (VAC)	Working voltage (VDC)	Creepage (mm, Min.)	Clearance (mm, Min.)	Package
NQ1H (X)	1	5, 12, 15, 24	3.3, 5, 9, 12, 15 ±3.3, ±5, ±9, ±12, ±15, +15/-9	5000	300	6 (9 for X type)	6 (9 for X type)	SIP 7
NQ2H (X)	2	5, 12, 15, 24	3.3, 5, 9, 12, 15 ±3.3, ±5, ±9, ±12, ±15, +15/-9	5000	300	6 (9 for X type)	6 (9 for X type)	SIP 7
NB3R5HW	3.5	4.5-18, 9-36, 18-75	5, 12, 15, ±5, ±12, ±15	5000	250	8	8	DIP 16
NC10HW	10	4.5-18, 9-36, 18-75	5, 12, 15, ±5, ±12, ±15	5000	250	8	8	DIP 24
ND20HW	20	9-36, 18-75	5, 12, 15, ±5, ±12, ±15	5000	250	8	8	1.6x1
NJ30HW	30	9-36, 18-75	5, 12, 15, ±5, ±12, ±15	5000	250	8	8	2x1

* (X) means 2mm PIN pitch



ISO 9001 / ISO 14001 / IECQ QC080000
 Tel : +886-6-384 2366 (Rep.) Fax : +886-6-384 2399
 E-mail : sales@motien.com.tw Web : www.motien.com.tw
 Copyrights ©2023 MOTIEN TECHNOLOGY CO., LTD.® All Rights Reserves.

